

Qty: 2 Ref: 13.9-7010 Schedule 13-9 : Special sign	No through route to Harvil Roed via Newyears Green Lane follow diversion	Qty: 3 Ref: 2704 Direction of temporary diversion route	Diverted traffic
Qty: 2 Ref: 13.9-7010 Schedule 13-9 : CCTV in operation	CCTV in operation	Qty: 2 Ref: 573 Direction to hazard right	
Qty: 1 Ref: 13.9-7010 Schedule 13-9 : information sign	Businesses open as usual	Qty: 2 Ref: 573 Direction to hazard left	
Qty: 2 Ref: 13.9-7010 Schedule 13-9 : Special sign	No through route to Breakspear Road South via Newyears Green Lane follow diversion	Qty: 4 Ref: 7001 Road works ahead	
Qty: 2 Ref: 2702 Start of temporary diversion route	Diversion	Qty: 2 Ref: 7010-FP-13-9 Nature of temporary hazard ahead - Road Closed	ROAD CLOSED
Qty: 3 Ref: 2702 Start of temporary diversion route	Diversion	Qty: 7 Ref: 7010.1 Nature of temporary hazard ahead - Road Ahead Closed	ROAD AHEAD CLOSED
Qty: 2 Ref: 2702 End of temporary diversion route	Diversion ENDS		
Qty: 2 Ref: 2703 Direction of temporary diversion route from junction ahead	Diverted traffic		
Qty: 2 Ref: 2703 Direction of temporary diversion route from junction ahead	Diverted traffic		
Qty: 3 Ref: 2704 Direction of temporary diversion route	Diverted traffic		



SAFETY ZONE DIMENSIONS S
Permanent speed limit 30mph or less
Sideways safety zone 0.5m
Longways safety zone 0.5m
(Dimensions are minima)

Drawing Office					
DWG Number	VH8862	- 1MC03-SCJ_VHW-HW-P	LN-S000-001111		
Revision	0	Date Surveyed	09/09/25		
Drawn By	RQ	Date Drawn	09/09/25		
Survey By	RQ	Phase Number	1 of 1		
Checked By	PT	Page Number	1 of 3		

Area of Works
Safety Zones
750mm Road Signs
750mm/1m Road Cones
Trojan Barriers

Newyears Green Lane, Harefield, Uxbridge, UB9 6LT

Site Details Address

1.Do not scale from this drawing, all dimensions to be verified on site.

2. It will be the responsibility of the contractor to ensure that all temporary traffic management shall be in accordance with the Traffic Signs Manual chapter 8 2009, Safety at Street works 2013, Traffic Signs Regulations and General Directions 2016 and all current / relevant Health and safety legislation.

3. All signage placement will be subject to available safe working space and all signage will be secured / ballasted with straps or sandbags.

Drawing Notes

4. A minimum lateral safety zone of 0.5M will be maintained at all times.

5. A minimum running lane of 3.0m will be maintained for buses and HGV's and a minimum of 2.5m for cars and light vehicles.

6. A safe segregated working area will be provided and maintained at all times.
7. Minimum size of temporary signage will be 750mm.

8. Airlock system to be utilised where practicable.
9. A minimum of 1.0m to be maintained for pedestrian access

Road Closure & Diversion